



MM INCHES

	XS / 700	S / 900	M / 900	L / 900	XL / 900	XXL
A HEAD TUBE ANGLE / ANGLE TUBE DE DIRECTION	67.0°	67.0°	67.0°	67.0°	67.0°	67.0°
B HEAD TUBE LENGTH / HAUTEUR TUBE DE DIRECTION	100.0 MM	100.0 MM	110.0 MM	125.0 MM	135.0 MM	150.0 MM
C TOP TUBE HORIZONTAL / LONGUEUR HORIZONTALE TUBE SUPÉRIEUR	545.0 MM	575.0 MM	595.0 MM	625.0 MM	645.0 MM	675.0 MM
D STANDOVER HEIGHT / HAUTEUR ENTRE-JAMBES	728.0 MM	767.0 MM	790.0 MM	812.0 MM	845.0 MM	878.0 MM
E BB OFFSET / DEPORT AXE DE PÉDALIER	-44.0 MM	-60.0 MM	-60.0 MM	-60.0 MM	-60.0 MM	-60.0 MM
F BB HEIGHT / HAUTEUR AXE DE PÉDALIER	308.5 MM	316.0 MM	316.0 MM	316.0 MM	316.0 MM	316.0 MM
G WHEEL BASE / ENTRAXE ROUES	1,104.0 MM	1,147.0 MM	1,169.4 MM	1,201.5 MM	1,223.0 MM	1,255.1 MM
H BB CENTER TO TOP TUBE CENTER / DIST. BOITIER - MILIEU TUBE SUPÉRIEUR						
I BB CENTER TO TOP OF SEAT TUBE / DIST. BOITIER - SOMMET TUBE DE SELLE	355.0 MM	395.0 MM	440.0 MM	480.0 MM	530.0 MM	580.0 MM
J SEAT ANGLE / ANGLE TUBE DE SELLE	75.0°	75.0°	75.0°	75.0°	75.0°	75.0°
K CHAINSTAY / LONGUEUR DES BASES	445.0 MM	457.0 MM	457.0 MM	457.0 MM	457.0 MM	457.0 MM
L REACH / REACH	390.7 MM	411.7 MM	429.2 MM	455.5 MM	473.0 MM	499.3 MM
M STACK / STACK	576.0 MM	609.5 MM	618.5 MM	632.5 MM	641.7 MM	655.5 MM
N STEM LENGTH / LONGUEUR POTENCE	45.0 MM	45.0 MM	45.0 MM	60.0 MM	75.0 MM	75.0 MM
O TRAIL / CHASSE AU SOL	104.0 MM	109.6 MM	109.6 MM	109.6 MM	109.6 MM	109.6 MM